

Features and Characteristics

Alumilite designs reliable products produced with the best available materials, and we stand behind them with superior customer service. Please contact us for more information.

Housing: A heavy duty spun aluminum shroud is welded to the 8" casting and sealed to prevent water entry. The dome cap covers driver compartment and is secured with three stainless steel flat head screws.

Dome Cap: Cast aluminum dome houses driver assembly and is secured to the arm with stainless steel hardware.


Lens Assembly: Clear tempered glass is sealed to hinged door frame and secured with three stainless steel fasteners.

Decorative Arm: Extruded aluminum arm with decorative band is welded to form a one piece bracket. The arm is secured to the pole tenon with four stainless steel fasteners.

Module/Driver: HP Winner LED Modules have high quality Lumiled LED's with an IP-68 rating and waterproof connectors. They are available in type 3, 4 and 5 distributions with 35w/4500lm, 55w/6100lm, 70w/9000lm and 110w/12,200lm. Modules are available in 3000, 4000 and 5000k and have a minimum CRI of 80. Drivers are 0-10v dimming with universal voltage. Extruded aluminum heat sinking system provides optimal thermal management.

Finish: Polyester powder coating on all metal parts. Color to be specified.

Listing: Luminaire is ETL listed for wet locations.



Specifications

Series	Wattage/Lamp	Volts
VK-21	35w/LED = 35/LED	UV
VK-21	55w/LED = 55/LED	UV
VK-21	70w/LED = 70/LED	UV
VK-21	110w/LED = 11/LED	UV

Options	Finish
WM = Wall Mount	BZ = Bronze
1A = Single Pole Mount	BK = Black
2A = Twin Pole Mount	WH = White
30k = 3000k R3 = Type 3	SL = Silver
40k = 4000k R4 = Type 4	CC = Custom Color
50k = 5000k R5 = Type 5	

Example

70 Watt LED, 120 Volts, Wall Mount, 5000k, Type 3, Bronze
VK-2170/LED-UV/WM/50k/R3/BZ