

Features and Characteristics

Alumilite designs reliable products produced with the best available materials, and we stand behind them with superior customer service. Please contact us for more information.

Top Cap: Aluminum top cap is easily removed to access the module. Cap is gasketed and secured to the lens assembly with one flush stainless steel screw.

Lens/Reflector: Clear acrylic enclosure is sealed to the top cap and the shaft. Internal satin aluminum reflector system produces a smooth symmetrical distribution. Optional with 90 or 180 degree house shields "9HS"/"18HS"

Shaft Construction: Four extruded aluminum interlocking sections form the 8" square shaft. Two sections are welded to lens assembly. The upper section slides up to access anchor bolts. Available in different heights.

Anchor Base: Heavy duty cast aluminum base is provided with three 3/8"x 8" plated anchor bolts.

Module/Driver: LED modules are TerraLux linear fully-integrated with patented Thermal Management Technology to provide maximum light output at all times. Modules are IP-65 rated and have universal voltage and 0-10v dimming. 16w/800lm, 26w/1300 lm or 30w/1720 lm. Available in 3000, 3500 and 4000k.

Finish: Polyester powder coating baked on finish.

Listing: Luminaire is ETL listed for wet locations.



Specifications

Series	Wattage/Lamp	Volts	Height
AB-TR	16w/LED= 816/LED	UV	24"
AB-TR	26w/LED= 826/LED	UV	30"
AB-TR	30w/LED= 830/LED	UV	36"
			42"
			48"

Options

3000k = 30k

3500k = 35k

4000k = 40k

SP = 10kv Surge Protector

PH = Button Cell

9HS = 90° Shield

18HS = 180° Shield

Finish

BZ = Bronze

BK = Black

WH = White

SL = Silver

CC = Custom Color

Example

40 Watt, LED, 120 Volts, 24" Tall, 3500k, Bronze

AB-TR-840/LED-UV/24"/35k/BZ