

Features and Characteristics

Alumilite designs reliable products produced with the best available materials, and we stand behind them with superior customer service. Please contact us for more information.

Top Cap: Aluminum dome cap is secured to louver assembly with one stainless tamper resistant fastener.

Enclosure: Clear acrylic enclosure is sealed to the top cap and the shaft. Internal glass refractor with type 5 distribution is standard. Optional with type 3 refractor "RF3". House shields available in 90 or 180 degrees.

Shaft Construction: Four heavy gauge .188 wall extruded aluminum interlocking sections form the bollard shaft. Two sections are internally welded to base plate and two sections are welded at louver assembly. The upper section can side up to access anchor bolts and power supply.

Base Plate: Heavy duty cast aluminum base is provided with three (3) 3/8" X 8" zinc plated anchor bolts, nuts and washers.

Module/Driver: Cree modules are incased in a cast aluminum housing and sealed with diffused lens. 20w/2000lm, 30w/3000lm and 40w/4000lm modules are available in 3000, 3500 and 4000k. Drivers are universal voltage and 0-10v dimming. Optional with emergency driver "EMD".

Finish: Polyester powder coating on all metal parts.

Listing: Luminaire is ETL listed for wet locations.



Specifications

Series	Wattage/Lamp	Volts	Height
DB-RF	20w/LED = 820/LED	UV	24"
DB-RF	30w/LED = 830/LED	UV	30"
DB-RF	40w/LED = 840/LED	UV	36"
			42"
			48"

Options

3000k = 30k

3500k = 35k

4000k = 40k

PH = Butoon Cell

EMD = Emergency Driver

9HS = 90° Shield

18 HS = 180° Shield

RF3 = Type 3 Refractor

Finish

BZ = Bronze

BK = Black

WH = White

SL = Silver

CC = Custom Color

Example

26 Watt, LED, 120 Volts, 24" Tall, 3500k, Bronze

DB-RF-826/LED-UV/24"/35k/BZ